

IN-5530/BC1-0047

## AMENDMENTS TO THE CLAIMS

Please amend the claims as indicated below.

1. (Previously Presented) An aqueous coating material comprising a product formed by mixing with one another
  - (A1) at least one base color containing less than 5% by weight water that imparts at least one of color and effect comprising
    - (a11) at least one binder, wherein the binder is optionally water-soluble or water-dispersible,
    - (a12) at least one pigment that provides at least one of color and effect, and
    - (a13) at least one organic solvent, wherein the organic solvent is optionally water-miscible, and optionally, at least one of
    - (a14) at least one crosslinking agent,
    - (a15) at least one auxiliary, and
    - (a16) at least one additive;
  - (A2) at least one aqueous color-imparting base color comprising
    - (a21) at least one water-soluble or -dispersible binder,
    - (a22) at least one color pigment, and
    - (a23) water, and optionally, at least one of
    - (a24) at least one organic solvent, wherein the organic solvent is optionally water-miscible,
    - (a25) at least one crosslinking agent,
    - (a26) at least one auxiliary, and
    - (a27) at least one additive;
- and
- (B) at least one aqueous, pigment-free mixing varnish comprising
  - (b1) at least one water-soluble or -dispersible binder, and

IN-5530/BC1-0047

- (b2) water,  
and optionally, at least one of
  - (b3) at least one crosslinking agent,
  - (b4) at least one auxiliary, and
  - (b5) at least one additive;  
and optionally
  - (C) a pigment-free aqueous medium comprising
    - (c1) at least one rheology control additive;optionally, with the proviso that at least one of the additives (a16), (a27), and (b5) further comprise at least one rheology control additive (c1).
2. (Previously Presented) A modular system for preparing aqueous coating materials comprising
- (I) at least one module containing less than 5% by weight water that provides at least one of color and effect comprising
    - (A1) at least one base color that imparts at least one of color and effect comprising
      - (a11) at least one binder, wherein the binder is optionally water-soluble or water-dispersible,
      - (a12) at least one pigment that imparts at least one of color and effect, and
      - (a13) at least one organic solvent, wherein the organic solvent is optionally water-miscible,  
and optionally, at least one of
      - (a14) at least one crosslinking agent,
      - (a15) at least one auxiliary, and
      - (a16) at least one additive;
  - (II) at least one aqueous color module comprising
    - (A2) at least one aqueous color-imparting base color comprising
      - (a21) at least one water-soluble or -dispersible binder,
      - (a22) at least one color pigment, and

IN-5530/BC1-0047

- (a23) water,
  - and optionally, at least one of
  - (a24) at least one organic solvent, wherein the organic solvent is optionally water-miscible,
  - (a25) at least one crosslinking agent,
  - (a26) at least one auxiliary, and
  - (a27) at least one additive;
- and
- (III) at least one aqueous, pigment-free mixing varnish module comprising
    - (B) at least one pigment-free mixing varnish comprising
      - (b1) at least one water-soluble or -dispersible binder, and
      - (b2) water,
      - and optionally, at least one of
      - (b3) at least one crosslinking agent,
      - (b4) at least one auxiliary, and
      - (b5) at least one additive;
- and optionally,
- (IV) at least one pigment-free rheology module comprising
    - (C) an aqueous medium comprising
      - (c1) at least one rheology control additive;
- optionally, with the proviso that at least one of the additives (a16), (a27), and (b5) further comprise at least one rheology control additive (c1).

3. (Previously Presented) A process for preparing an aqueous coating material with precisely defined shade and optical effect comprising mixing modules differing in material composition and function and stored separately from one another, shortly before application of the coating material, wherein the modules comprise
- (I) at least one module containing less than 5% by weight water that provides at least one of color and effect comprising

IN-5530/BC1-0047

- (A1) at least one base color containing less than 5% by weight water that imparts at least one of color and effect comprising
    - (a11) at least one binder, wherein the binder is optionally water-soluble or water-dispersible,
    - (a12) at least one pigment that imparts at least one of color and effect, and
    - (a13) at least one organic solvent, wherein the organic solvent is optionally water-miscible,and optionally, at least one of
    - (a14) at least one crosslinking agent,
    - (a15) at least one auxiliary, and
    - (a16) at least one additive;
  - (II) at least one aqueous color module comprising
    - (A2) at least one aqueous color-imparting base color comprising
      - (a21) at least one water-soluble or -dispersible binder,
      - (a22) at least one color pigment, and
      - (a23) water,and optionally, at least one of
      - (a24) at least one organic solvent, wherein the organic solvent is optionally water-miscible,
      - (a25) at least one crosslinking agent,
      - (a26) at least one auxiliary, and
      - (a27) at least one additive;
- and
- (III) at least one pigment-free mixing varnish module comprising
    - (B) at least one aqueous, pigment-free mixing varnish comprising
      - (b1) at least one water-soluble or -dispersible binder, and
      - (b2) water,and optionally, at least one of
      - (b3) at least one crosslinking agent,
      - (b4) at least one auxiliary, and

IN-5530/BC1-0047

- (b5) at least one additive;  
and optionally  
(IV) at least one pigment-free rheology module comprising  
(C) an aqueous medium comprising  
(c1) at least one rheology control additive;  
optionally, with the proviso that at least one of the additives (a16), (a27), and  
(b5) further comprise at least one rheology control additive (c1).
4. (Previously Presented) The aqueous coating material of claim 1, wherein the base color (A1) imparts one of i) effect or ii) color and effect.
5. (Previously Presented) The modular system of claim 2, wherein the modular system comprises one of
1. at least one color module (I) containing less than 5% by weight water, at least one aqueous color module (II), and at least one aqueous, pigment-free mixing varnish module (III),
  2. at least one color and effect module (I) containing less than 5% by weight water, at least one aqueous color module (II), and at least one aqueous, pigment-free mixing varnish module (III), or
  3. at least one effect module (I) containing less than 5% by weight water, at least one color module (I) containing less than 5% by weight water, at least one aqueous color module (II), and at least one aqueous, pigment-free mixing varnish module (III).
6. (Previously Presented) The coating material of claim 1, wherein the additive (b5) comprises at least one rheology control additive.
7. (Previously Presented) The coating material of claim 1 further comprising the pigment-free, aqueous medium (C), and wherein the rheology control additive (c1) is provided only in the pigment-free, aqueous medium (C).

IN-5530/BC1-0047

8. (Previously Presented) The modular system of claim 2, wherein the modular system further comprises the at least one pigment-free rheology module (IV).
9. (Previously Presented) The aqueous coating material of claim 1, wherein the binders (a11), (a21), and (b1) come from the same polymer class.
10. (Previously Presented) The aqueous coating material of claim 9, wherein the binders (a11), (a21), and (b1) are polyurethane resins.
11. (Previously Presented) The aqueous coating material of claim 1, wherein the binders (a21) and (b1), and optionally the binder (a11), comprise functional groups that can be converted into anions by at least one of neutralizing agents and anionic groups.
12. (Withdrawn) A method comprising applying the aqueous coating material of claim 1 to a substrate to provide one of an automotive OEM finish, an automotive refinish, and a plastic coating.
13. (Withdrawn) A method comprising applying the aqueous coating material of claim 1 to a substrate as a basecoat, and applying to the basecoat the aqueous coating material of claim 1 as a solid-color topcoat to provide one of an automotive OEM finish, an automotive refinish, and a plastic coating.
14. (Presently Amended) A coating ~~comprising a coating process product~~ prepared by a process comprising applying the aqueous coating material of claim 1 to a substrate to provide an applied coating material and curing the applied coating material to provide a coating.
15. (Previously Presented) The coating of claim 14, wherein the coating comprises a multicoat coating system, wherein the multicoat coating system is

IN-5530/BC1-0047

formed by a wet-on-wet technique, and wherein the multicoat coating system is at least one of a color coating system and an effect coating system.

16. (Canceled)
17. (Previously Presented) The modular system of claim 2, wherein the base color (A1) imparts one of i) effect or ii) color and effect.
18. (Previously Presented) The process of claim 3, wherein the base color (A1) imparts one of i) effect or ii) color and effect.
19. (Previously Presented) The process of claim 3, wherein the mixing modules comprise one of
  1. at least one color module (I) containing less than 5% by weight water, at least one aqueous color module (II), and at least one aqueous, pigment-free mixing varnish module (III),
  2. at least one color and effect module (I) containing less than 5% by weight water, at least one aqueous color module (II), and at least one aqueous, pigment-free mixing varnish module (III), and
  3. at least one effect module (I) containing less than 5% by weight water, at least one color module (I) containing less than 5% by weight water, at least one aqueous color module (II), and at least one aqueous, pigment-free mixing varnish module (III).
20. (Previously Presented) The modular system of claim 2, wherein the additive (b5) comprises at least one rheology control additive.
21. (Previously Presented) The process of claim 3, wherein the additive (b5) comprises at least one rheology control additive.

IN-5530/BC1-0047

22. (Previously Presented) The process of claim 3, wherein the aqueous coating material further comprises the at least one pigment-free rheology module (IV).
23. (Previously Presented) The modular system of claim 2, wherein the binders (a11), (a21), and (b1) come from the same polymer class.
24. (Previously Presented) The modular system of claim 23, wherein the binders (a11), (a21), and (b1) are polyurethane resins.
25. (Previously Presented) The process of claim 3, wherein the binders (a11), (a21), and (b1) come from the same polymer class.
26. (Previously Presented) The process of claim 25, wherein the binders (a11), (a21), and (b1) are polyurethane resins.
27. (Previously Presented) The modular system of claim 2, wherein the binders (a21) and (b1), and optionally the binder (a11), comprise functional groups that can be converted into anions by at least one of neutralizing agents and anionic groups.
28. (Previously Presented) The process of claim 3, wherein the binders (a21) and (b1), and optionally the binder (a11), comprise functional groups that can be converted into anions by at least one of neutralizing agents and anionic groups.
29. (Withdrawn) A method comprising applying the modular system of claim 2 to a substrate to provide one of an automotive OEM finish, an automotive refinish, and a plastic coating.
30. (Withdrawn) The process of claim 3 further comprising applying the aqueous coating material to a substrate to provide one of an automotive OEM finish, an automotive refinish, and a plastic coating.



IN-5530/BC11-0047

31. (Withdrawn) A method comprising applying the modular system of claim 2 to a substrate as a basecoat, and applying to the basecoat the modular system of claim 2 as a solid-color topcoat to provide one of an automotive OEM finish, an automotive refinish, and a plastic coating.
32. (Withdrawn) The process of claim 3 further comprising applying the aqueous coating material to a substrate as a basecoat, and applying to the basecoat the aqueous coating material as a solid-color topcoat to provide one of an automotive OEM finish, an automotive refinish, and a plastic coating.
33. (Presently Amended) A coating comprising ~~a coating process product of comprising the result of applying the modular system of claim 2 to a substrate to provide an applied coating and curing the applied coating to provide a coating.~~
34. (Canceled) The coating produced by the process of claim 32.
35. (Canceled)
36. (Previously Presented) The coating of claim 33, wherein the coating comprises a multicoat coating system, wherein the multicoat coating system is formed by a wet-on-wet technique, and wherein the multicoat coating system is at least one of a color coating system and an effect coating system.
37. (Canceled)
38. (Canceled)
39. (Previously Presented) The coating of claim 34, wherein the coating comprises a multicoat coating system, wherein the multicoat coating system is

IN-5530/BC140047

formed by a wet-on-wet technique, and wherein the multicoat coating system is at least one of a color coating system and an effect coating system.

40. (Canceled)

41. (Canceled)